B19/SB19 SERIES



The thirst quenchers!



- ✓ Stylish high gloss black and stainless look cabinet
- ✓ Available in hot/cold or cool/cold
- ✓ Accommodates the Waterworks[™] Self fill bottle and standard bottles
- √ 3.3L stainless steel cold tank



- ✓ Hygienic, easy to use push taps
- ✓ Hot water safety tap
- 3 year comprehensive warranty

B19/SB19 SERIES

GENERAL FEATURES

With its high gloss front, brushed steel sides and stylish slim design, the B19 series cooler is perfect for any home or office.

COLD TANK: 3.3 litre type 304 stainless steel for superior chilling. The highly polished surface is easy to clean and maintain.

HOT TANK: 1.8 litre type 304 stainless steel with 500 watt sheathed heater to ensure temperature control. The on/off switch is easily accessible at the back of the unit.

CABINET: Black high gloss front with brushed steel silver sides. The top and front panels are moulded ABS plastic and the side panels are high polymer polyester coated steel.

TAPS: NSF approved. The hygienic, self-closing push taps are made from durable polypropylene. Hot safety tap comes standard on hot/cold model.

OPTIONAL EXTRAS

SELF-FILL BOTTLE: A flexible filtration option for home, office or factory. Just fill with tap water for a continuous supply of fresh water. The SFB is the perfect partner for all bottled coolers and ceramic dispensers.

NON SPLASH VALVE: Allows the bottle to be changed without excess spillage. Simply place the bottle on the cooler and the valve opens to let the water through. When removing the bottle, the valve automatically closes.

Waterworks

Waterworks[™] Australia

ABN 91 902 793 936

48-50 Neumann Road Capalaba Queensland 4157 Bulk Warehouse: 53 Neumann Road Capalaba Queensland 4157

SPECIFICATIONS

REFRIGERATION: Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an overload protector. Lubricant is not needed.

ELECTRICAL: Certificate number 160793. 220v 50hz single phase. A 1.5 metre power cord is supplied. Full load current is 1.2 amps.

PERFORMANCE

Tap 1 Approx. 4-10°C

Tap 2 Room temperature

Hot tap Approx. 84-89°C

CAPACITY

ROOM TEMP °C	21	27	32			
150ML CUPS/HR 10°C	44	32	18			
LITRES/HR AT 10°C	4.2	3.1	1.8			
HOT WATER DELIVERY: 15 x 170ml cups per hour						

^{*}Intermittent use only, continuous use will result in reduced performance.

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
B19C	17kg	B19CH	18kg	29cm	34cm	101cm
SB19C	15kg	SB19CH	16kg	29cm	51cm	53cm

WARRANTY

The entire range of Waterworks™ 19 Series water coolers are covered by our 3 Year Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 3 year from the date of original sale.

Damage to the stainless steel tank may occur if using reverse osmosis or incorrect filtration.

Warranty will be void in the event of this happening.

Please discuss filtration options with your local water filter specialist.

Distributed by		

Phone (07) 3390 3777

Email sales@waterworksaustralia.com

www.waterworksaustralia.com